

DH-IPC-HFW2100

1.3Megapixel HD Network Mini IR-Bullet Camera



Features

- 1/3" 1.3Megapixel progressive scan Aptina CMOS
- H.264 & MJPEG dual-stream encoding
- Max 15fps@1.3M(1280×960)&25/30fps@720P(1280×720)
- Day/Night(ICR), 2DNR, AWB, AGC, BLC
- Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS
- 6mm fixed Lens (3.6mm, 8mm optional)
- Max. IR LEDs length 20m
- IP66, PoE

DH-IPC-HFW2100

Technical Specifications

Model		DH-IPC-HFW2100P		DH-IPC-HFW2100N	
Camera					
Image Sensor		1/3" 1.3Megapixel Aptina CMOS			
Effective Pixels		1280(H)x960(V)			
Scanning System		Progressive			
Electronic Shutter Speed		Auto/Manual, 1/3~1/10000s		Auto/Manual, 1/4~1/10000s	
Min. Illumination		Color: 0. 1LUX/F1.2, B/W: 0.005LUX/F1.2; 0LUX/F1.2(IR on)			
S/N Ratio		>50dB			
Camera Features					
Max. IR LEDs Length		20m			
Day/Night		Auto(ICR) / Color / B/W			
Backlight Compensation		BLC			
White Balance		Auto			
Gain Control		Auto/Manual			
Noise Reduction		2D			
Privacy Masking		Up to 4 areas			
Lens					
Focal Length		6mm (3.6mm,8mm optional)			
Max Aperture		F1.8			
Angle of View		H: 46°(70°/35°)			
Mount Type		Board-in Type			
Video					
Compression		H.264 / MJPEG			
Resolution		1.3M(1280×960) / 720P(1280×720) / D1(704×576) / CIF(352×288)		1.3M(1280×960) / 720P(1280×720) / D1(704×480) / CIF(352×240)	
Frame Rate	Main Stream	1.3M(1~15fps)/720P(1 ~ 25/30fps)			
	Sub Stream	D1/CIF(1 ~ 25/30fps)			
Bit Rate		H.264: 32K ~ 8192Kbps, MJPEG: 32K ~ 12288Kbps			
Network					
Ethernet		RJ-45 (10/100Base-T)			
Protocol		IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour			
ONVIF		ONVIF Ver. 2.0			
Max. User Access		10 users			
Smart Phone		iPhone, iPad, Android, Windows Phone			
General					
Power Supply		DC12V, PoE(802.3af)			
Power Consumption		<6W			
Working Environment		-10°C~+60°C, 10%~90%			