
1.3Megapixel HD Network PTZ Dome Camera



DH-SD6580-HN: 18x optical zoom, 1.3M CCD, 12/15fps@1.3M, 25/30fps@720P, IP67, Dahua HD Block Camera

DH-SD6581-HN: 18x optical zoom, 1.3M CCD, 12/15fps@1.3M, 25/30fps@720P, IP67, Hitachi HD Block Camera

Features

Camera & Video

- 1/3" 1.3Megapixel SONY Progressive Scan CCD
- Powerful 18x optical zoom and 12x digital zoom
- H.264 & Dual-stream video encoding and JPEG image capture
- 12/15fps@1.3M(1280×960) & 25/30fps@720P resolution
- Day/Night(ICR), Auto iris, Auto focus, AWB, BLC
- Up to 24 privacy masking areas
- Built-in Web server, NVR, CMS(PSS/DSS) & DMSS

Dome Drive

- Max 400 °/s pan speed, 360° continuous pan rotation & auto flip with no blind spot monitor
- Up to 255 preset, 5 auto scan, 8 tour, 5 pattern
- Auto recognition of general protocols such as DH-SD, Pelco-P/D, and etc
- Speed setup according to the focal distance, auto rotation speed adjust in accordance with the lens zoom rate
- Auto restore to previous PTZ and lens status after power failure
- Time Task: Auto activation of Preset/Scan/Tour/ Pattern by preset-time

- Idle Motion: Call preset/tour and etc operations after idle for the specified time (including the idle status after the system boots up)
- OSD and operation prompts of various languages
- Build-in 7/2 channel alarm input/output
- Intelligent 3D positioning function
- IP67 all-environments protection, 4000V thunder-proof, auto constant temperature & anti-fog
- Easy installation with user-friendly designs

Specifications

Model	DH-SD6580-HN		DH-SD6581-HN	
Camera				
Image Sensor	1/3" 1.3M Progressive Scan CCD			
Effective Pixels	1296(H) x 966(V)			
Lens	18x optical zoom			
	f=4.5mm(Wide)~81mm(Tele), F1.6~F2.7		f=4.7mm(Wide)~84.6mm(Tele), F1.6~F2.8	
Digital Zoom	12x			
Horizontal Viewing Angle	51.6°(Wide)~3.1°(Tele)		55.2°(Wide)~3.2°(Tele)	
Min. Object Distance	10mm(wide) ~ 1000mm(Tele)			
Min. Illumination	0.1Lux/F1.6(Color), 0.01Lux/F1.6(B/W)		0.5Lux/F1.6(Color), 0.02Lux/F1.6(B/W)	
Electronic Shutter	NTSC:1/4~1/10000s, PAL:1/3~1/10000s, 20level			
White Balance	Auto/ATW/Indoor/Outdoor/Manual			
BLC	ON/OFF			
WDR	/		ON/OFF	
Day/Night	Auto(ICR) / Color / B/W			
S/N Ratio	More than 50 dB			
Privacy Masking	ON/OFF (up to 24 privacy masking areas)			
Analog Video Output	BNC(1.0Vp-p / 75Ω), PAL / NTSC			
Video & Audio				
Video Compression	H.264 / MPEG4			
Image Resolution	1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / CIF(352×288/352×240) / QCIF(176×144/176×128)			
Encoding Speed	Main Stream	PAL: 1.3M(1~12fps), 720P(1~25fps)		
		NTSC: 1.3M(1~15fps), 720P(1~30fps)		
	Extra Stream	PAL: D1/CIF/QCIF (1~25fps)		
		NTSC: D1/CIF/QCIF (1~30fps)		
Bit Rate	32K~8Mbps			
Audio Compression	G.711a(32Kbps) / AMR(10.2Kbps)			
Audio Mode	Off/Audio input/Audio output			
Dome Drive				
Pan/Tilt Range	Horizontal: 0°~360°endless, Vertical: -2°~90° auto flip 180° to continue monitor			
Manual Control Speed	Horizontal: 0.1°~300°/s, Vertical: 0.1°~150°/s			
Preset Speed	Horizontal: 400°/s, Vertical: 180°/s			

Preset	255
PTZ Mode	5 Auto Pattern, 8 Auto Tour, 5 auto scan
3D Positioning	Yes
Speed Setup	Human-oriented focal Length/ speed adaptation
Info Display	Time, Location, Dome title, Dome coordinates, Temperature, Alarm, and etc.
Power up Action	Auto restore to previous PTZ and lens status after power failure
Idle Motion	Activate preset/scan/tour/ patter if there is no command in the specified period.
Time Task	Auto activation of Preset/Scan/Tour/ Pattern by preset-time
Alarm	7/2 alarm input/output, Triggering Preset/Tour/Pattern/Scan//Alarm output
Protocol	DH-SD, Pelco-P/D, Auto recognition of general protocols
Network	
Ethernet	RJ-45 (10/100Base-T)
Network Functions	HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server
Max Remote Users	20 Users simultaneously
Processor	TI DaVinci Series DSP
Operating System	Embedded LINUX
Resource	Simultaneous remote monitoring, remote operation & local recording
Remote Operation	Monitor, PTZ control, Voice Intercom, System setting, Playback, File download, Log information, Maintenance & Upgrade
Local Recording	SD/SDHC, Max 32GB
User Interface	WEB, CMS(DSS/ PSS), DMSS, NVR
General	
Power Supply	AC 24V/3A(±10%)
Power Consumption	12W(Indoor), 50W(Outdoor, heater on)
Working Temperature	-40°C ~ 60°C
Working Humidity	<90%
Protection Level	IP67, 4000V thunder, surge and wave protection
Dimension	Φ222(mm) x 322(mm)
Weight	5.0kg